

# Contents

<b>Preface</b>	<b>v</b>
<b>Notation</b>	<b>xi</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Limited data rate . . . . .	2
1.2 Outline and contributions . . . . .	3
<b>2 Control networks</b>	<b>7</b>
2.1 Control over networks . . . . .	7
2.2 How control networks work . . . . .	8
2.2.1 Periodic pattern . . . . .	8
2.2.2 Medium access methods . . . . .	9
2.2.3 A protocol example . . . . .	10
2.3 Application examples . . . . .	12
2.3.1 Jacking systems of train cars . . . . .	12
2.3.2 Networks on automobiles . . . . .	13
2.3.3 Process control . . . . .	14
<b>3 Distributed control over networks</b>	<b>15</b>
3.1 The switch box problem . . . . .	15
3.2 Preliminaries . . . . .	17
3.3 Stabilization using PTV local controllers . . . . .	19
3.4 Assignability measure analysis . . . . .	23
3.5 Multiple mobile robot example . . . . .	25
<b>4 Finite data rate control — single-input case</b>	<b>33</b>
4.1 Dwell-time switched systems and their stability . . . . .	33
4.2 Quadratic stabilization of sampled-data systems . . . . .	35
4.2.1 Problem formulation . . . . .	35
4.2.2 Control Lyapunov function approach . . . . .	37
4.2.3 Bounds on trajectories . . . . .	40
4.2.4 Solution to the sampled-data problem . . . . .	42

4.3	Quantized sampled-data control . . . . .	47
4.3.1	Problem formulation . . . . .	48
4.3.2	A sufficient condition for stability . . . . .	49
4.3.3	Solution to the quantized sampled-data problem . . . . .	51
4.4	Finite quantizers . . . . .	60
4.5	Control over a finite data rate channel . . . . .	63
4.5.1	Data rate for control . . . . .	63
4.5.2	Time delay analysis . . . . .	64
4.5.3	Time delay and quantization . . . . .	68
4.6	Design of $\sigma$ . . . . .	70
4.7	Magnetic ball levitation example . . . . .	72
<b>5</b>	<b>Towards data rate reduction</b>	<b>83</b>
5.1	Time-varying quantization . . . . .	83
5.1.1	Problem formulation . . . . .	83
5.1.2	A switching law . . . . .	85
5.1.3	Magnetic ball levitation example continued . . . . .	88
5.2	Nonuniform sampling . . . . .	89
5.3	Dwell-time switching control . . . . .	90
5.3.1	Dwell-time switched systems with logarithmic partitions . . . . .	91
5.3.2	Problem formulation . . . . .	93
5.3.3	Hybrid automata representation . . . . .	94
5.3.4	Solution to the dwell-time switching problem . . . . .	98
5.4	Finite partition dwell-time switching . . . . .	101
5.4.1	Dwell-time switched systems with finite partitions . . . . .	102
5.4.2	State feedback control . . . . .	103
5.4.3	State feedback under measurement noise . . . . .	104
5.4.4	Observer-based output feedback . . . . .	106
5.4.5	Cart-pendulum system example . . . . .	109
<b>6</b>	<b>Extensions for the multiple input case</b>	<b>117</b>
6.1	Quadratic stabilization of sampled-data systems . . . . .	117
6.1.1	Problem formulation . . . . .	117
6.1.2	Generalization of the setup . . . . .	119
6.1.3	Bounds on trajectories . . . . .	122
6.1.4	Solution to the sampled-data problem . . . . .	125
6.2	Quantized sampled-data control . . . . .	128
6.2.1	Problem formulation . . . . .	128
6.2.2	Solution to the quantized sampled-data problem . . . . .	129
6.3	Dwell-time switching control . . . . .	140
6.3.1	Dwell-time switched systems with logarithmic partitions . . . . .	140
6.3.2	Problem formulation . . . . .	143
6.3.3	Solution to the dwell-time switching problem . . . . .	144

6.4	Design of $S$ . . . . .	147
6.4.1	A sufficient condition for $S > I$ . . . . .	148
6.4.2	Extension of the design method for $\sigma$ . . . . .	149
6.4.3	A design method for $S > I$ . . . . .	150
6.5	Two cart-pendulum system example . . . . .	152
<b>7</b>	<b>Conclusion</b> . . . . .	<b>161</b>
	<b>Bibliography</b> . . . . .	<b>163</b>
	<b>Symbol Index</b> . . . . .	<b>170</b>
	<b>Subject Index</b> . . . . .	<b>172</b>



<http://www.springer.com/978-3-540-43237-1>

Limited Data Rate in Control Systems with Networks

Ishii, H.; Francis, B.A.

2002, XII, 180 p., Softcover

ISBN: 978-3-540-43237-1