

Contents

- 1 Serving Many Mobile Users in Various Scenarios: Radios to Go Smart(er) and Cognitive 1**
 - 1.1 Towards Cognitive Radio 1
 - 1.2 Increasing the Hardware Flexibility 1
 - 1.2.1 Wireless Landscape Giving Challenges and Opportunities 2
 - 1.2.2 The Software-Defined Radio Solution 4
 - 1.3 Increasing the Policy Flexibility 4
 - 1.3.1 Spectrum: A Scarce Resource 5
 - 1.3.2 The Opportunistic Spectrum Access Solution 5
 - 1.4 Cognitive Radio: Exploiting Flexibility with Intelligent Control 7
 - 1.5 The Need for a New Approach 9
 - 1.6 Radios to Go Smarter and Cognitive 9

- 2 Emerging Standards for Smart Radios: Enabling Tomorrow’s Operation 11**
 - 2.1 Standards in Evolution 11
 - 2.2 Hardware Flexibility 12
 - 2.2.1 IEEE 802.11: A Flexible Radio Becomes Smarter 13
 - 2.2.2 3GPP-LTE Evolutions 18
 - 2.3 Spectrum Access Flexibility 23
 - 2.3.1 The ISM Band: Coexistence in Unlicensed Bands 24
 - 2.3.2 The TV White Spaces: Spectrum Sharing in Licensed Bands 26
 - 2.4 Operation Across Technologies: Cognitive Radio 31
 - 2.4.1 Mobile Independent Handover: IEEE 802.21 31
 - 2.4.2 Dynamic Spectrum Access Networks: IEEE DYSPAN 32
 - 2.4.3 Reconfigurable Radio Systems: ETSI RSS 34

- 3 Cognitive Radio Design and Operation: Mastering the Complexity in a Systematic Way 37**
 - 3.1 The Need for a Strategy 37
 - 3.2 The Design Landscape Is No Longer Flat 38

| | | |
|----------|---|-----------|
| 3.3 | Design Challenges and Opportunities | 39 |
| 3.3.1 | Design Time Complexity | 39 |
| 3.3.2 | The Mountains We Have to Climb | 40 |
| 3.3.3 | The Sharing Challenge | 42 |
| 3.3.4 | Run-Time Complexity | 43 |
| 3.4 | Proposed Control Framework | 44 |
| 3.4.1 | General Design Concepts | 44 |
| 3.4.2 | Design-Time Flow | 46 |
| 3.4.3 | Run-Time Operation | 50 |
| 3.5 | Conclusions | 53 |
| 4 | Distributed Monitoring for Opportunistic Radios | 55 |
| 4.1 | To Not Interfere | 55 |
| 4.1.1 | Problem Context | 55 |
| 4.1.2 | Smart Aspect | 56 |
| 4.1.3 | Outdoor 802.11 Measurements | 57 |
| 4.2 | The Sensing Problem | 59 |
| 4.3 | Distributed Distance-to-Contour Estimation | 59 |
| 4.3.1 | Algorithm Overview and Design Decisions | 59 |
| 4.3.2 | Local Channel Estimation | 61 |
| 4.3.3 | Distance-to-Contour Flooding | 63 |
| 4.3.4 | Iterative Power Control | 66 |
| 4.3.5 | Results | 67 |
| 4.4 | Conclusions | 70 |
| 5 | Coexistence: The Whole Is Greater than the Sum of Its Parts | 73 |
| 5.1 | Introduction | 73 |
| 5.2 | Modeling Coexistence | 74 |
| 5.2.1 | IEEE 802.15.4 Network Model | 74 |
| 5.2.2 | IEEE 802.11 Interference Model | 75 |
| 5.2.3 | Performance and Energy Measures | 76 |
| 5.3 | Basic Solution: Random Frequency Selection | 77 |
| 5.4 | The Problem from a Different Angle | 77 |
| 5.5 | Scan-Based Approaches | 78 |
| 5.6 | Distributed Learning and Exploration | 79 |
| 5.6.1 | General Framework | 79 |
| 5.6.2 | Learning Engine | 80 |
| 5.6.3 | Exploration Algorithms | 80 |
| 5.7 | Simulation Results | 83 |
| 5.8 | Conclusions | 84 |
| 6 | Anticipative Energy and QoS Management: Systematically Improving the User Experience | 87 |
| 6.1 | Energy Efficiency for Smart Radios | 87 |
| 6.1.1 | Minimum Energy at Sufficient QoS | 87 |
| 6.1.2 | Smart Aspects and Energy Efficiency | 88 |
| 6.2 | Anticipation Through Design Time Modeling | 89 |

| | | |
|-------------------|---|------------|
| 6.2.1 | Flexibility for Energy and QoS | 90 |
| 6.2.2 | The Varying Context | 92 |
| 6.2.3 | Objectives for Efficient Energy and QoS Management . . . | 94 |
| 6.2.4 | Anticipating the Performance | 95 |
| 6.3 | Managing the User Experience | 98 |
| 6.3.1 | Smart Resource Allocation Problem Statement | 98 |
| 6.3.2 | Greedy Resource Allocation | 99 |
| 6.4 | IEEE 802.11a Design Case | 101 |
| 6.4.1 | Energy-Performance Anticipation | 102 |
| 6.4.2 | Anticipative Control in the 802.11 MAC Protocol | 104 |
| 6.5 | Adapting to the Dynamic Context | 106 |
| 6.6 | Conclusions | 107 |
| 7 | Distributed Optimization of Local Area Networks | 109 |
| 7.1 | Introduction | 109 |
| 7.2 | Existing Flexibility and Control Mechanisms | 110 |
| 7.2.1 | Optimization of IEEE 802.11 Networks | 110 |
| 7.2.2 | Benchmark Solution: Spatial Backoff | 112 |
| 7.2.3 | Multi-Agent Learning | 113 |
| 7.3 | Spatial Learning: Distributed Optimization of IEEE 802.11 Networks | 114 |
| 7.3.1 | The General Framework | 114 |
| 7.3.2 | The Control Dimensions | 116 |
| 7.3.3 | System Scenarios | 117 |
| 7.3.4 | Design-Time Procedures | 118 |
| 7.3.5 | The Learning Engine | 120 |
| 7.3.6 | Seeding the Learning Engine with the DT Procedures . . . | 121 |
| 7.3.7 | Implementation in the IEEE 802.11 MAC Protocol | 122 |
| 7.4 | Assessing the Gains | 124 |
| 7.5 | Conclusions | 128 |
| 8 | Close | 129 |
| 8.1 | “Good Enough” Is “Close Enough to Optimal” | 129 |
| 8.2 | Closing Remarks: The End Is Not There nor in Sight | 131 |
| 8.2.1 | Keep Moving with the Target | 131 |
| References | | 133 |

Software Defined Radios

From Smart(er) to Cognitive

Pollin, S.; Timmers, M.; Van der Perre, L.

2011, XX, 140 p., Hardcover

ISBN: 978-94-007-1277-5