

# Preface

The generalized and programmable nature of Field Programmable Gate Arrays (FPGAs) has made them a popular choice for the implementation of digital circuits. However, the programmability of FPGAs makes them larger, slower, and more power consuming than their counterpart ASICs; hence making them unsuitable for applications requiring high density, performance, and low power consumption. The main theme of this work is to improve the area of FPGAs. For this purpose, a detailed exploration and optimization of two FPGA architectures is performed: one is the well-known mesh-based FPGA architecture while the other is tree-based architecture that remains relatively unexplored despite its better performance and routing predictability. Further, a detailed comparison between the two architectures is presented to highlight their respective advantages and disadvantages.

The exploration and optimization of two architectures start with the introduction of heterogeneous hard-blocks in both architectures. In this work, first we present a new environment for exploration of tree-based heterogeneous FPGA architecture. This environment is flexible in nature and allows to explore different architecture techniques with varying types of hard-blocks. Further, in this work, we present an exploration environment for mesh-based heterogeneous FPGA architecture. The two environments are used to explore a number of techniques for both architectures. These techniques are later evaluated using different heterogeneous benchmarks that are placed and routed on the two architectures using a specifically developed software flow. A detailed comparison between different techniques of the two architectures is performed and results show that on average, tree-based architecture gives better overall results than mesh-based architecture.

Generalized mesh and tree-based FPGA architectures are further improved by turning them into application-specific FPGAs. An application-specific inflexible FPGA (ASIF) is a modified FPGA with reduced flexibility and improved density. This work initially presents a new tree-based homogeneous ASIF and when compared to an equivalent tree-based FPGA, it gives 64% area gain. Further, the comparison between equivalent mesh and tree-based ASIFs shows that tree-based ASIF gives 12% better area results than mesh-based ASIF. We also extend the

ASIF to the heterogeneous domain and experimental results show that, on average, tree-based heterogeneous ASIF gives 70% area gain when compared to equivalent tree-based heterogeneous FPGA. Further, the comparison between heterogeneous mesh and tree-based ASIFs reveals that tree-based ASIF gives either equal or better results than mesh-based ASIF.

Tree-based Heterogeneous FPGA Architectures  
Application Specific Exploration and Optimization

Farooq, U.; Marrakchi, Z.; Mehrez, H.

2012, XVI, 188 p., Hardcover

ISBN: 978-1-4614-3593-8