

Contents

1	Introduction	1
	References	3
2	Background Theory	5
2.1	Carbon	5
2.1.1	Hybridization of s and p Orbitals	5
2.1.2	Allotropes of Carbon	7
2.2	Band Structure: Graphite to Graphene	10
2.2.1	3D Model of Graphite	10
2.2.2	Graphene's Band Structure	15
2.2.3	Bilayer Graphene	18
2.2.4	Summary	22
2.3	Graphite Nanoparticles	22
2.4	Percolation in Composites	23
2.4.1	Percolation Theory	24
2.4.2	Electrical Percolation	24
2.4.3	Carbon Black Example	26
2.5	Tunneling	29
2.5.1	Current Density Through a Barrier	30
2.5.2	Supply Function	32
2.5.3	Tunneling Probability	33
2.5.4	Tsu-Esaki Equation	35
2.6	Summary	35
	References	36
3	Fabrication and Measurement	39
3.1	Sample Fabrication	39
3.1.1	Chemical Properties of Pristine Silicone Rubber	39
3.1.2	Composite Mixing	41
3.2	Composite Mounts	43
3.2.1	Rigid PCB Mount	43
3.2.2	Flexible Acetate Mount	44
3.2.3	Imprint Lithography	46

3.3	Naphthalene Molecules for Absorption onto Graphite	47
3.4	Measurement	49
3.4.1	Four Terminal Measurement.	49
3.4.2	Current–Voltage Measurement	50
3.4.3	Low Temperature Measurement	51
3.4.4	Oscillation Frequency Measurement	51
3.5	Bend Induced Bilayer Strain	52
3.5.1	Room Temperature Bend	52
3.5.2	Low Temperature Bend	53
3.5.3	Calculation of Bilayer Strain	54
3.6	Differential Pressure Array	55
3.6.1	Concept	55
3.6.2	Design	56
3.6.3	Electronics	57
3.6.4	Composite Pixels	58
3.6.5	Data Collection.	60
3.7	Summary	61
	References	61
4	Tunneling Negative Differential Resistance in a GSC.	63
4.1	Introduction	63
4.2	Results	64
4.2.1	Negative Differential Resistance	64
4.2.2	Volume Fraction Dependence.	65
4.2.3	Electric Field Domains	66
4.2.4	Crystalline Structure of Conductive Particles	67
4.2.5	Temperature Dependence.	68
4.2.6	Particle Orientations	69
4.2.7	Embedded Bilayer.	71
4.2.8	NDR Mechanism in a Graphite–Silicone Composite	71
4.3	Modelling the Current Across a Graphite–Silicone–Graphite Domain	73
4.3.1	Barrier Width	75
4.3.2	Barrier Height	76
4.4	Discussion	78
4.4.1	Joule Heating	78
4.4.2	Applications	80
4.4.3	Summary of NDR Mechanism	80
4.5	Conclusion	82
	References	82
5	Electromechanical Properties and Sensing	85
5.1	Introduction	85
5.2	The Maxwell Model of Viscoelasticity.	88

5.3	Methods	91
5.3.1	Precision Bending to Induce Bilayer Strain	91
5.3.2	AC Impedance Measurements	91
5.3.3	Ultrasound Pressure Measurements in Water	92
5.3.4	Differential Pressure Array Test Procedure.	94
5.4	Results	96
5.4.1	Steady State Piezoresistance with Bilayer Strain.	96
5.4.2	Transient Piezoresistance Due to Viscoelasticity.	101
5.4.3	Bandwidth and Capacitance with Strain.	104
5.4.4	Detection of Acoustic Pressure from Ultrasound.	107
5.4.5	Differential Pressure Array Imaging	112
5.5	Summary	115
	References	116
6	Electronic Amplification in the NDR Region	119
6.1	Introduction	119
6.2	Oscillator Circuit Theory	121
6.3	Lambda Diode Example.	123
6.3.1	Lambda Diode Oscillator.	124
6.3.2	Lambda Diode Amplifier.	130
6.3.3	Summary of the Lambda Diode	133
6.4	Active Response of the GSC in the NDR Region	134
6.4.1	Sustaining Oscillations in the NDR Region	134
6.4.2	Strain Dependant Oscillations.	140
6.4.3	Strain Tunable Intrinsic Frequency Mode.	144
6.4.4	Strain-Tuned Flexible Amplifier via NDR	147
6.5	Summary	148
	References	150
7	Conclusions and Future Work	153
7.1	Future Research.	155
7.1.1	Towards Room Temperature NDR	155
7.1.2	A High Resolution Flexible Skin	156
7.2	Concluding Remarks	156
	References	157
	Appendix A: Procedure for Imprint Lithography Stamp	159
	Appendix B: ICP-RIE Recipe for Deep Silicon Etch	161
	Appendix C: Synthesis of Silane Functionalized Naphthalenediimide.	163
	Appendix D: Calculation of Cut-Off Frequency	165

Electrical Properties of Graphite Nanoparticles in
Silicone

Flexible Oscillators and Electromechanical Sensing

Littlejohn, S.D.

2014, XV, 166 p. 92 illus., 82 illus. in color., Hardcover

ISBN: 978-3-319-00740-3