

Contents

1	Introduction to Piezoelectric Accelerometers with Integral Electronics (IEPE)	1
1.1	Principle, Construction, and Block Diagram of IEPE Accelerometers	1
1.2	PE Accelerometer Used Without Electronics and Its Comparison with an IEPE Accelerometer	5
1.3	Characteristics of IEPE Accelerometers	8
1.3.1	Sensitivity	8
1.3.2	Range or Dynamic Range	9
1.3.3	Transfer Function and Frequency Response	9
1.3.4	Resonant Frequency	13
1.3.5	Temperature Response	13
1.3.6	Transverse Sensitivity	15
1.3.7	Amplitude Linearity	15
1.3.8	Total Harmonic Distortion	15
1.3.9	DC Output Bias Voltage	16
1.3.10	Full Scale Output Voltage	16
1.3.11	Output Impedance	17
1.3.12	Noise Floor	18
1.3.13	Warm-Up Time	18
1.3.14	Overload Recovery	19
1.3.15	Temperature Range	19
1.3.16	Sinusoidal Vibration Limit	20
1.3.17	Shock Limit	20
1.3.18	Base Strain Sensitivity	21
1.3.19	Size and Weight	21
1.4	Types of IEPE Accelerometers	22
1.4.1	Charge Mode IEPE Accelerometer	22
1.4.2	Voltage Mode IEPE Accelerometers	29

1.4.3	IEPE Accelerometers with Ground Isolation. Ground Loop Issue	34
1.4.4	IEPE Accelerometers with Transducer Electronic Data Sheet	35
	References	39
2	Piezoelectric Transducers Used for Piezoelectric Accelerometers with Integral Electronics	43
2.1	Function of a PE Transducer in an IEPE Accelerometer	43
2.2	Transfer Function of a PE Transducer	44
2.3	Equivalent Electrical Schematic of a PE Transducer and Its Main Electrical Characteristics	45
2.4	Constructions of the PE Transducers Used in the IEPE Accelerometers	47
2.4.1	Compression Mode Design	47
2.4.2	Shear Mode Design	48
2.4.3	Flexural or Bending Mode Design	50
2.4.4	Comparison Between Compression, Shear, and Flexural Mode Designs	53
2.5	Piezoelectric Elements Used in the IEPE Accelerometers	53
2.5.1	Quartz Piezoelectric Element	53
2.5.2	Lead Zirconate Titanate Piezoceramic Element	54
2.5.3	Comparison Between IEPE Sensors Using PZT Piezoceramic and Quartz Sensitive Elements	55
2.5.4	The Pyroelectric Effect	55
	References	55
3	Integral Amplifiers Used for IEPE Accelerometers	59
3.1	Charge Amplifier	59
3.1.1	Configuration of a FET-BJT Charge Amplifier	60
3.1.2	Configuration of a Charge Amplifier Based on an Op Amp	61
3.1.3	Performance Characteristics of Charge Amplifiers	63
3.2	Voltage Amplifier	65
3.2.1	Configurations of the Voltage Amplifiers	66
3.2.2	Performance Characteristics of a Voltage Amplifier	67
3.3	Other Performance Characteristics of Charge and Voltage Amplifiers	69
3.3.1	Noise or Noise Floor	69
3.3.2	DC Output Bias Voltage	70
3.3.3	Full Scale or Maximum Linear Output Voltage	71
3.3.4	Gain Stability	71
3.3.5	Amplitude Linearity and Total Harmonic Distortion	71
3.3.6	Input and Output Impedances	72
3.3.7	Power Requirements: Voltage Supply and Current Supply	72

3.3.8	Temperature Range	72
3.3.9	Size and Shape of the Hybrid Circuit Board	73
3.4	Technology, Components, and Materials Used for Amplifier Circuits	73
3.4.1	Resistors	74
3.4.2	Capacitors	74
3.4.3	JFETs vs. MOSFETs in FET-Input Amplifiers	75
	References	76
4	Noise of a FET Amplifier	79
4.1	Equivalent Noise Circuit of a FET Amplifier	80
4.2	Noise Analysis and Noise Sources of the FET Amplifier	83
4.2.1	FET Thermal Noise	83
4.2.2	Thermal Noise Caused by the Load Resistance	83
4.2.3	Thermal Noise Caused by the Biasing Resistor	84
4.2.4	1/f Noise of JFETs and MOSFETs	85
4.2.5	Shot Noise Current in the Gate	86
4.2.6	Overall Equivalent Noise Voltage Referred to the FET Input	87
4.2.7	Some Practical Examples	88
4.2.8	Comparison Between Theoretical and Measurement Results	89
4.2.9	1/f Noise and Thermal Noise of JFET 2N4338 Measurement Results	90
	References	91
5	Comparison of 1/f Noise and Thermal Noise in JFETs and MOSFETs	93
5.1	Introduction to 1/f Noise and Thermal Noise in JFETs and MOSFETs	93
5.2	Low-Noise Measurement System for Measurement of 1/f Noise and Thermal Noise in JFETs and MOSFETs	94
5.2.1	Preamplifier	95
5.2.2	Major Amplifier	97
5.3	Measurement Results of the 1/f Noise and Thermal Noise in JFETs and MOSFETs	97
5.3.1	N-Channel JFETs 1/f and Thermal Noise Measurement Results	100
5.3.2	N-Channel MOSFETs 1/f and Thermal Noise Measurement Results	102
5.3.3	P-Channel MOSFETs 1/f and Thermal Noise Measurement Results	103
5.4	Summary and Discussion of the Measurement Results	105
	References	106

6	Fundamental Noise Limit of an IEPE Accelerometer	107
6.1	When and Why Noise of a PE Transducer Should Not Be Neglected	107
6.2	The PE Transducer's Noise Sources Description	108
6.3	Equivalent Electrical Noise Schematic of a PE Transducer	108
6.4	The PE Transducer's Mechanical-Thermal Noise	110
6.5	The PE Transducer's Electrical-Thermal Noise	112
6.6	Complete Expression for the Fundamental Noise Limit of an IEPE Accelerometer	114
6.7	Some Practical Examples	115
	References	116
7	Noise of an IEPE Accelerometer	117
7.1	Introduction	117
7.2	Equivalent Noise Schematic of the IEPE Accelerometer and General Noise Expressions Derivation	118
7.3	Noise of the FET-Input Amplifier	123
7.3.1	The FET Thermal Noise e_{nt}	123
7.3.2	The FET 1/f Noise $e_{n1/f}$	124
7.3.3	The FET Noise e_{ns} Caused by the Shot Noise Current i_{ns} in the Gate Circuit	125
7.3.4	Total Noise e_{nFET} Generated by the FET Noise Sources	126
7.3.5	Thermal Noise Sources e_{nRb} and e_{nRl} Caused by the FET Biasing Resistor R_b and Resistor R_l , Respectively	126
7.3.6	Total Noise e_{namp} Generated by the FET-Input Amplifier Noise Sources	127
7.4	Noise of the PE Transducer	128
7.5	Overall Noise of the IEPE Accelerometer	129
7.6	Comparison Between Theoretical and Experimental Results	129
	References	132
8	Ultra-Low-Noise IEPE Seismic Accelerometers	135
8.1	Introduction	136
8.2	Configuration of the Designed Accelerometers	136
8.3	Construction of the Designed Accelerometers	138
8.4	Characteristics of the Designed Accelerometers	139
8.5	Key Factors Providing Ultra-Low-Noise in the Designed Accelerometers	144
8.6	Direct Measurement of the Designed Accelerometer's Noise	145
	References	148
9	High-Temperature, Up to 175 °C, Miniature IEPE Accelerometers	151
9.1	Introduction	152

9.2 Configuration and Performance Characteristics of the Designed
175 °C Triaxial IEPE Accelerometers Having Sensitivities
100 mV/g and 10 mV/g and Size of 14.8 mm³ 153

9.3 Configuration and Performance Characteristics of the Designed
175 °C Triaxial IEPE Accelerometers Having Sensitivities
10, 1, and 0.5 mV/g and Size of 10 mm³ 155

9.4 Configuration and Characteristics of the Designed 175 °C,
10 mV/g Triaxial IEPE Accelerometers with Size of 10 mm³
and Comprising 2-Pole Active LPF 158

9.5 Configuration and Characteristics of the Designed 175 °C,
10 mV/g Single Axis IEPE Accelerometers Comprising
2-Pole Active LPF 158

9.6 Key Factors Providing High-Temperature Operations
in the Designed Accelerometers 165

References 168

Piezoelectric Accelerometers with Integral Electronics

Levinzon, F.

2015, XV, 169 p. 99 illus., 37 illus. in color., Hardcover

ISBN: 978-3-319-08077-2