

# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Radio Frequency Identification	1
1.1.1	RFID System Components	2
1.1.2	Tag	2
1.1.3	Reader	3
1.1.4	Application Host	3
1.2	Wireless Sensor Networks	3
1.2.1	Evolution of Sensor Network	4
1.2.2	Wireless Sensor Network Components	4
1.2.3	Architecture of WSN	6
1.2.4	WSN Characteristics	8
1.2.5	Routing Protocols in WSN	9
1.2.6	Energy Aware Routing in WSN	9
1.3	Why Integration of RFID and WSN	10
1.4	Difference Between RFID and WSN	10
	References	11
<b>2</b>	<b>RFIDs and WSNs</b>	<b>13</b>
2.1	Radio Frequency Identification (RFID)	13
2.1.1	Frequency	14
2.1.2	Tag-Reader Communication	14
2.2	RFID System Components	16
2.2.1	Tag	16
2.2.2	Reader	16
2.3	Types of Tags	16
2.3.1	Tags by the Power Source	17
2.3.2	Tags by the Memory Type	18
2.3.3	Tags by the Wireless Communication Signal	18

2.4	Routing in WSNs . . . . .	18
2.4.1	Routing Challenges and Design Issues . . . . .	19
2.4.2	Routing Objectives . . . . .	20
2.4.3	Characteristics of Routing Protocols . . . . .	21
2.5	Routing Techniques in Wireless Sensor Networks. . . . .	21
2.5.1	Flat Routing . . . . .	22
2.5.2	Hierarchical Protocols . . . . .	22
2.5.3	Location-Based Protocols. . . . .	23
2.5.4	Multipath Routing Protocols . . . . .	23
2.5.5	Query Based Routing Protocols . . . . .	23
2.5.6	Negotiation Based Routing Protocols . . . . .	23
2.5.7	QoS-Based Routing Protocols . . . . .	24
2.6	Routing Protocols for WSN . . . . .	24
2.6.1	Directed Diffusion Protocol . . . . .	24
2.6.2	Low Energy Adaptive Clustering Hierarchical Protocol (LEACH) . . . . .	26
2.6.3	Sensor Protocol for Information via Negotiation (SPIN). . . . .	28
2.6.4	ACtive QUery Forwarding In sensoR nEtworks Protocol (ACQUIRE). . . . .	29
2.6.5	Geographical Adaptive Fidelity Protocol (GAF) . . . . .	31
2.6.6	Dynamic Source Routing (DSR) . . . . .	33
	References . . . . .	34
<b>3</b>	<b>Challenges and Issues in the WSN and RFID.</b> . . . .	<b>37</b>
3.1	Contemporary Work . . . . .	37
3.2	Issues and WSN and RFID. . . . .	42
3.3	Solution to the Challenges . . . . .	42
	References . . . . .	44
<b>4</b>	<b>The Delay Model for ACQUIRE.</b> . . . .	<b>47</b>
4.1	Basic Concept. . . . .	47
4.2	Main Challenges. . . . .	48
4.3	Network Delay Changes Caused by Routing Events . . . . .	48
4.4	Delay Techniques . . . . .	49
4.5	The Delay Model . . . . .	50
4.5.1	Timeliness Monitoring . . . . .	50
4.5.2	Definitions and Notations. . . . .	50
4.5.3	End-to-End Delay Estimation Using Probability Technique . . . . .	50
4.5.4	End-to-End Latency Estimation . . . . .	51
4.6	Energy Estimation . . . . .	52
4.7	Energy Analysis . . . . .	53
4.7.1	Basic Definition and Notation . . . . .	53
4.7.2	Cost of Energy in Updating . . . . .	54
4.7.3	Total Energy Cost. . . . .	54
	References . . . . .	55

<b>5</b>	<b>Simulator for Smart Node</b>	<b>57</b>
5.1	Proposed Solution to the Challenges	57
5.2	Simulator Architecture Design Issues	58
5.2.1	Embedded Architecture Design	59
5.3	Simulation Tasks and Requirements	62
5.3.1	Requirements and Issues for Integrated Sensor	62
5.3.2	Requirements and Issues for Data Delivery	64
5.4	Implementation of Simulator	65
5.4.1	Design	66
5.4.2	Data Flow	66
5.4.3	Memory Architecture	68
5.4.4	Memory Organization	69
5.4.5	Command Structure	70
	References	72
<b>6</b>	<b>Simulations Based Case Study and Analysis</b>	<b>73</b>
6.1	Network Model	73
6.1.1	Node	73
6.1.2	Zone	74
6.1.3	Link	74
6.2	Routing Model	75
6.2.1	Cost Function	75
6.2.2	Energy Consumption Rate	75
6.2.3	Packet Energy	75
6.2.4	Available Energy	75
6.2.5	Path Cost	76
6.3	Simulation Model	76
6.4	Case Study Scenario for Simulation	76
6.5	Analysis of Case Study Simulation	77
6.5.1	Energy Model	78
6.5.2	Delay Model	78
6.6	Recommendation of Models on the Basis of Simulation	79
6.7	Analysis of Proposed Simulator	84

RFID-WSN Integrated Architecture for Energy and Delay-Aware Routing

A Simulation Approach

Ahmed, J.; Siyal, M.Y.; Tayyab, M.; Nawaz, M.

2015, XII, 89 p. 36 illus., 22 illus. in color., Softcover

ISBN: 978-981-287-413-9