

# Contents

|          |   |           |
|----------|---|-----------|
| <b>1</b> | <b>Introduction</b>   | <b>1</b>  |
| 1.1      | Status Quo and Trends of Interconnected Systems               | 1         |
| 1.2      | Stability Problems of Interconnected Systems                  | 3         |
| 1.3      | WAMS Technology and Its Application in Interconnected Systems | 4         |
| 1.4      | Low-Frequency Oscillation Analysis Methods                    | 5         |
| 1.5      | Challenges of Wide Area Dynamic Monitoring and Control        | 7         |
|          | References  | 9         |
| <b>2</b> | <b>Theoretical Foundation of Low-Frequency Oscillations</b>   | <b>13</b> |
| 2.1      | The Basic Principles of Low-Frequency Oscillation             | 13        |
| 2.1.1    | Local Mode  | 14        |
| 2.1.2    | Inter-Area Mode   | 16        |
| 2.2      | Techniques Based on System Model                              | 19        |
| 2.2.1    | Linearization of the State Equation                           | 20        |
| 2.2.2    | Calculation of Eigenvalues and Eigenvectors                   | 21        |
| 2.2.3    | Determination of Oscillation Parameters                       | 22        |
| 2.2.4    | Brief Summary of System Model Analysis Techniques             | 23        |
| 2.3      | Techniques Based on Measured Information                      | 24        |
| 2.3.1    | Discrete Fourier Transform                                    | 24        |
| 2.3.2    | Prony Algorithm and Multi-Prony                               | 26        |
| 2.3.3    | Wavelet Transform and Its Improvements                        | 29        |
| 2.3.4    | Hilbert–Huang Transform                                       | 31        |
| 2.4      | Summary   | 36        |
|          | References  | 36        |

|          |  |           |
|----------|--|-----------|
| <b>3</b> | <b>Oscillatory Parameters Computation Based on Improved HHT . . .</b>                    | <b>39</b> |
| 3.1      | Introduction of Improved Empirical Mode Decomposition (EMD) . . . . .                    | 39        |
| 3.1.1    | The Selection of Stop Criterion for Sifting in EMD . . .                                 | 39        |
| 3.1.2    | End Effects and Extrema Symmetrical Extension . . . .                                    | 41        |
| 3.1.3    | Mode-Mixing and Frequency Heterodyne Technique (FHT) . . . . .                           | 44        |
| 3.1.4    | The Improved EMD Based on ESE and FHT . . . . .  | 50        |
| 3.2      | Time and Frequency Analysis of Intrinsic Mode Function . . . .                           | 51        |
| 3.3      | Normalized Hilbert Transform (NHT) . . . . .   | 53        |
| 3.3.1    | Decompose the IMF into AM and FM Parts . . . . .   | 54        |
| 3.3.2    | Calculation of the Instantaneous Frequency . . . . .                                     | 55        |
| 3.3.3    | Calculation of the Instantaneous Amplitude and Damping Ratio . . . . .                   | 56        |
| 3.4      | The Flowchart of the Improved HHT . . . . .  | 56        |
| 3.5      | Summary . . . . .  | 57        |
|          | References . . . . .   | 58        |
| <b>4</b> | <b>Oscillation Model Identification Based on Nonlinear Hybrid Method (NHM) . . . . .</b> | <b>59</b> |
| 4.1      | Identification of Dominant Oscillation Mode . . . . .                                    | 59        |
| 4.2      | The Processing of Oscillation Mode Identification . . . . .                              | 61        |
| 4.2.1    | Calculation of the Absolute Phase (AP) and Relative Phase (RP) of IMF. . . . .           | 61        |
| 4.2.2    | Determination of Node Contribution Factor (NCF) . . . .                                  | 62        |
| 4.2.3    | Computation of Approximate Mode Shape (AMS) . . . .                                      | 63        |
| 4.2.4    | Coherency of the Measured Signals . . . . .  | 64        |
| 4.2.5    | Flowchart of the Nonlinear Hybrid Method (NHM) . . .                                     | 65        |
| 4.3      | Study Case . . . . .   | 67        |
| 4.4      | Summary . . . . .  | 74        |
|          | References . . . . .   | 74        |
| <b>5</b> | <b>Identification of Dominant Complex Orthogonal Mode (COM). . .</b>                     | <b>75</b> |
| 5.1      | Introduction of Spatial and Temporal Behaviors of Oscillation Mode . . . . .             | 75        |
| 5.2      | Construction of the Complex Ensemble Measurement Matrix . . . . .                        | 77        |
| 5.3      | Implementations of Complex Orthogonal Decomposition (COD) . . . . .                      | 78        |
| 5.3.1    | Complex Eigenvalues Decomposition (C-ED) . . . . .                                       | 78        |
| 5.3.2    | Complex Singular Value Decomposition (C-SVD) . . . .                                     | 79        |
| 5.3.3    | Augmented Matrix Decomposition (AMD) . . . . .   | 80        |
| 5.3.4    | Definition of Relevant COMs . . . . .  | 82        |
| 5.4      | Extraction of the Propagating Features . . . . .   | 83        |
| 5.4.1    | Spatial Energy Distribution . . . . .  | 83        |

|          |  |            |
|----------|--|------------|
| 5.4.2    | Temporal Dynamic Characteristics . . . . .   | 83         |
| 5.4.3    | Energy Contribution Factor (ECF) . . . . .   | 84         |
| 5.5      | The Flowchart of Proposed COD . . . . .  | 84         |
| 5.6      | Study Case . . . . .   | 85         |
| 5.6.1    | Description of Sliding Window . . . . .  | 85         |
| 5.6.2    | Sliding Window Recursive Algorithm (SWRA)<br>of COD. . . . .   | 86         |
| 5.6.3    | Applications of the COD-SWRA . . . . .   | 87         |
| 5.7      | Summary . . . . .  | 91         |
|          | References . . . . .   | 91         |
| <b>6</b> | <b>Basic Framework and Operating Principle of Wide-Area<br/>Damping Control . . . . .</b>                | <b>93</b>  |
| 6.1      | Basic Framework of Wide-Area Damping Control . . . . .   | 93         |
| 6.2      | Operating Principle of Wide-Area Damping Control . . . . .   | 95         |
| 6.3      | System Modeling . . . . .  | 98         |
| 6.3.1    | SMIB System with FACTS WADC . . . . .  | 98         |
| 6.3.2    | System Modeling Based on Direct Feedback<br>Linearization Theory. . . . .                                | 98         |
| 6.4      | Summary . . . . .  | 101        |
|          | References . . . . .   | 101        |
| <b>7</b> | <b>Coordinated Design of Local PSSs and Wide-Area Damping<br/>Controller . . . . .</b>                   | <b>103</b> |
| 7.1      | Overview of Optimization Method . . . . .  | 103        |
| 7.2      | Description of Sequence Design and Global Optimization<br>Method. . . . .                                | 104        |
| 7.2.1    | Structure of PSS and HVDC-WADC . . . . .   | 104        |
| 7.2.2    | Design Procedure . . . . .   | 104        |
| 7.3      | Methodological Implementation . . . . .  | 107        |
| 7.3.1    | Damping Distribution . . . . .   | 107        |
| 7.3.2    | Sequential Design. . . . .   | 107        |
| 7.3.3    | Global Optimization . . . . .  | 108        |
| 7.4      | Case Study . . . . .   | 109        |
| 7.4.1    | AC/DC Hybrid Interconnected Systems. . . . .   | 109        |
| 7.4.2    | Result of Damping Distribution . . . . .   | 110        |
| 7.4.3    | Design Result . . . . .  | 112        |
| 7.4.4    | Performance Validation. . . . .  | 114        |
| 7.5      | Summary . . . . .  | 118        |
|          | References . . . . .   | 119        |
| <b>8</b> | <b>Robust Coordination of HVDC and FACTS Wide-Area<br/>Damping Controllers . . . . .</b>                 | <b>121</b> |
| 8.1      | Overview of Wide-Area Damping Control. . . . .   | 121        |
| 8.2      | Description of Wide-Area Control Networks Using Multiple<br>Power Electronics-Based Controllers. . . . . | 122        |

|           |  |            |
|-----------|--|------------|
| 8.3       | Controller Design Formulation . . . . .  | 123        |
| 8.3.1     | Multi-objective Synthesis of Wide-Area Robust Control . . . . .                                    | 123        |
| 8.3.2     | Pole Placement in LMI Regions . . . . .  | 124        |
| 8.4       | Design Procedure of Wide-Area Robust Coordinated Control . . . . .                                 | 125        |
| 8.5       | Case Study . . . . .   | 126        |
| 8.5.1     | Choice of Suitable Wide-Area Control Signals . . . . .   | 126        |
| 8.5.2     | Robust Design of HVDC- and FACTS-WADC . . . . .  | 128        |
| 8.5.3     | Evaluation of Robust Performance . . . . .   | 130        |
| 8.5.4     | Nonlinear Simulation . . . . .   | 132        |
| 8.6       | Summary . . . . .  | 134        |
|           | References . . . . .   | 134        |
| <b>9</b>  | <b>Assessment and Choice of Input Signals for Multiple Wide-Area Damping Controllers . . . . .</b> | <b>137</b> |
| 9.1       | Overview of Signal Selection Methods . . . . .   | 137        |
| 9.2       | Description of Relative Gain Array and Residue Analysis . . . . .                                  | 138        |
| 9.2.1     | Power System Model . . . . .   | 138        |
| 9.2.2     | Residue Analysis Method . . . . .  | 139        |
| 9.2.3     | RGA Analysis Method . . . . .  | 139        |
| 9.3       | Signal Selection Procedure . . . . .   | 141        |
| 9.4       | Case Study . . . . .   | 143        |
| 9.4.1     | Preselection of Input Signal Candidates . . . . .  | 144        |
| 9.4.2     | Final Choice of Effective Input Signals . . . . .  | 145        |
| 9.4.3     | Comparison with Local Control and Other Wide-Area Control Pairs . . . . .                          | 147        |
| 9.4.4     | Design of Multiple HVDC- and FACTS-WADCs . . . . .   | 148        |
| 9.4.5     | Validation of Control Performance . . . . .  | 150        |
| 9.5       | Summary . . . . .  | 153        |
|           | References . . . . .   | 154        |
| <b>10</b> | <b>Free-Weighting Matrix Method for Delay Compensation of Wide-Area Signals . . . . .</b>          | <b>155</b> |
| 10.1      | Time-Delay Power System . . . . .  | 155        |
| 10.1.1    | Description of Delay Power System with Wide-Area Signals' Delay . . . . .                          | 156        |
| 10.1.2    | Stability Analysis of Time-Delay Power System . . . . .  | 158        |
| 10.2      | Description of Free-Weighting Matrices (FWMs) Method . . . . .                                     | 159        |
| 10.3      | General Configuration of FACTS-WADC Based on FWMs Approach . . . . .                               | 162        |
| 10.4      | FWMs Approach-Based FACTS-WADC Design . . . . .  | 163        |
| 10.5      | Cases Study . . . . .  | 169        |
| 10.5.1    | 4-Machine 2-Area System . . . . .  | 169        |
| 10.5.2    | 16-Machine 5-Area Test System . . . . .  | 171        |

|           |  |            |
|-----------|--|------------|
| 10.6      | Summary . . . . .  | 174        |
|           | References . . . . .   | 177        |
| <b>11</b> | <b>Design and Implementation of Delay-Dependent Wide-Area Damping Control for Stability Enhancement of Power Systems . . .</b>   | <b>179</b> |
| 11.1      | System Description. . . . .  | 179        |
| 11.2      | Hardware Design . . . . .  | 180        |
| 11.3      | Design of the Control Algorithm . . . . .  | 184        |
| 11.3.1    | Classic Phase Compensation Method . . . . .  | 184        |
| 11.3.2    | Delay-Dependent State-Feedback Robust Design Method. . . . .   | 186        |
| 11.3.3    | Delay-Dependent Dynamic Output-Feedback Control Method . . . . .   | 189        |
| 11.4      | Algorithm Implementation. . . . .  | 191        |
| 11.4.1    | Discrete-Time Model for the Hardware Controller . . . .  | 191        |
| 11.4.2    | Algorithm Flowchart. . . . .   | 194        |
| 11.5      | Experimental Results . . . . .   | 197        |
| 11.6      | Summary . . . . .  | 201        |
|           | References . . . . .   | 201        |
| <b>12</b> | <b>Design and Implementation of Parallel Processing in Embedded PDC Application for FACTS Wide-Area Damping Control. . . . .</b> | <b>203</b> |
| 12.1      | System Description. . . . .  | 203        |
| 12.2      | Design of the Embedded System . . . . .  | 205        |
| 12.3      | Implementation of the Embedded System . . . . .  | 207        |
| 12.3.1    | Data Receiving via Communication Network. . . . .  | 207        |
| 12.3.2    | Data Processing . . . . .  | 208        |
| 12.3.3    | Monitoring and Protection. . . . .   | 210        |
| 12.3.4    | Wide-Area Damping Controller . . . . .   | 212        |
| 12.3.5    | Control Output Through SPI and External DAC. . . . .   | 213        |
| 12.4      | Parallel Processing of the Embedded System . . . . .   | 215        |
| 12.5      | Experimental Result . . . . .  | 217        |
| 12.6      | Summary . . . . .  | 223        |
|           | References . . . . .   | 223        |

Interconnected Power Systems

Wide-Area Dynamic Monitoring and Control Applications

Li, Y.; Yang, D.; Liu, F.; Cao, Y.; Rehtanz, C.

2016, XV, 223 p. 143 illus., Hardcover

ISBN: 978-3-662-48625-2