

# Contents

<b>1</b>	<b>Planning of Distillation and Absorption Columns</b>	<b>1</b>
1.1	Planning Information	1
1.2	Mass Balance for the Separation Task	5
1.3	Separation Conditions	6
1.4	Vapour-Liquid Equilibrium [4]	6
1.4.1	The Ideal Equilibrium According to Raoult–Dalton	7
1.4.2	Equations of State	7
1.4.3	Equilibrium Models for Non-polar Materials Considering the Non-ideal Behaviour in the Liquid Phase Based on Pure Component Data	7
1.4.4	Equilibrium Models for Polar Components with High Non-ideal Behaviour in the Liquid Phase	7
1.5	Energy and Mass Balance in the Column	7
1.5.1	Mass Balance (Fig. 1.4)	7
1.5.2	Energy Balance (Fig. 1.5)	11
1.5.3	Required Column Diameter	17
1.6	Selection of Column Internals	18
1.7	Condensers [2]	19
1.8	Reboiler [2]	20
1.9	Vacuum Pumps [3]	21
1.10	Control Facilities [5]	23
1.11	Heating Systems with Steam or Hot Oil [3]	29
1.11.1	Heat Transfer Coefficients	29
1.11.2	Steam Heating [3]	29
1.11.3	Heating with Hot Oil [3]	32
1.12	Cooling Systems [3]	34
1.12.1	Cooling Water Circulation Systems	34
1.12.2	Comparison Between a Cooling Tower and an Air Cooler	34

1.12.3	Cooling Water by Evaporating a Refrigerant or Adiabatic Evaporation . . . . .	35
1.12.4	Direct Condensation in Columns [6] . . . . .	37
	References. . . . .	37
<b>2</b>	<b>Equilibria, Bubble Points, Dewpoints, Flash Calculations, and Activity Coefficients. . . . .</b>	<b>39</b>
2.1	Vapour Pressure Calculations . . . . .	39
2.2	Phase Equilibrium of Ideal Binary Mixtures. . . . .	39
2.3	Bubble Point Calculation . . . . .	44
2.4	Dew Point Calculation . . . . .	46
2.5	Dew Point Calculation of Vapour Containing Inert Gases . . . . .	47
2.6	Dew and Bubble Point Lines of Ideal Binary Mixtures . . . . .	49
2.7	The Bubble Point and Dew Point of Immiscible Mixtures . . . . .	51
2.8	Flash Calculations for Ideal Binary Mixtures [1] . . . . .	52
2.9	Calculation of the Equilibrium and the Bubble and Dew Point Temperatures of Ideal Multi-component Mixtures . . . . .	59
2.10	Flash Calculations for Ideal Multi-component Mixtures [2] . . . . .	62
2.11	Phase Equilibrium of Non-ideal Binary Mixtures . . . . .	64
2.12	Calculation of the Activity Coefficients . . . . .	70
2.12.1	Calculation According to Wilson for Miscible Components [8]. . . . .	71
2.12.2	Calculation According to NRTL for Partially Miscible Components with Two Liquid Phases [9] . . . . .	73
2.12.3	Calculation According to Uniquac for Components with a Miscibility Gap. . . . .	74
2.12.4	Critical Comparison of the Activity Coefficients Calculated Using Different Models . . . . .	75
2.13	Bubble Point, Dew Point, and Flash Separation for Non-ideal Binary Mixtures . . . . .	77
2.14	Non-ideal Multi-component Mixtures . . . . .	79
	Conclusion . . . . .	82
	References. . . . .	83
<b>3</b>	<b>Fractionation of Binary Mixtures. . . . .</b>	<b>85</b>
3.1	Material Balance. . . . .	85
3.2	Vapour–Liquid Equilibria . . . . .	87
3.2.1	Equilibria of Ideal Mixtures. . . . .	87
3.2.2	Equilibria of Non-ideal Mixtures. . . . .	90
3.3	Minimum Number of Trays and Minimum Reflux Ratio . . . . .	92
3.4	Conversion of the Minimum Number of Trays to the Actual Number of Trays [3]. . . . .	94
3.5	Determination of the Feed Tray According to Kirkbride [4]. . . . .	95
3.6	Graphical Determination of the Number of Trays According to McCabe–Thiele (Fig. 3.4) . . . . .	95

3.7	Calculation of the Number of Trays Using the McCabe–Thiele Method [5] . . . . .	99
3.8	Tray to Tray—Calculation Using the Flow Rates and Relative Volatility $\alpha$ [6] . . . . .	102
3.9	Analytical Calculation According to Smoker [7–10]. . . . .	105
3.10	Thermal Condition of the Feed [10] . . . . .	106
3.11	Column Loading in the Rectification and Stripping Section . . . .	110
3.12	Design Data for the Column Internals . . . . .	111
3.13	Fractionation of Non-ideal Binaries . . . . .	116
	References. . . . .	120
<b>4</b>	<b>Calculation of Multi-component Fractionation Plants . . . . .</b>	<b>121</b>
4.1	Basic Data for the Design. . . . .	121
4.1.1	Mass Balance for the Separation Task. . . . .	121
4.1.2	Calculation of the Average Relative Volatility $\alpha$ for Ideal Mixtures . . . . .	123
4.1.3	Component Distribution According to Relative Volatilities [1, 6] . . . . .	125
4.2	Short-Cut Method for Ideal Multi-component Mixtures [2–7] . . . . .	126
4.2.1	Calculation of the Minimum Number of Trays $N_{\min}$ for a Given Component Distribution According to Fenske [8] . . . . .	126
4.2.2	Calculation of the Components Distribution at the Minimum Number of Trays $N_{\min}$ . . . . .	127
4.2.3	Determination of the Minimum Reflux Ratio $R_{\min}$ According to Underwood [9]. . . . .	127
4.2.4	Conversion to the Real Number of Trays at a Real Reflux Ratio $R$ [10]. . . . .	128
4.2.5	Determination of the Feed Tray According to Kirkbride [11] . . . . .	128
4.3	Vapour and Liquid Loading of the Column . . . . .	128
4.4	Calculation of the Compositions on Theoretical Stages [12, 13] . . . . .	141
4.5	Fractionation of Non-ideal, Multi-component Mixtures . . . . .	146
	References. . . . .	151
<b>5</b>	<b>Extractive and Azeotropic Distillation . . . . .</b>	<b>153</b>
5.1	Extractive Distillation [1, 2] . . . . .	153
5.2	Azeotropic Distillation [3–8]. . . . .	154
5.2.1	Heteroazeotropic Distillation (Fig. 5.5) . . . . .	157
5.2.2	Entrainer Distillation (Fig. 5.9) . . . . .	158
5.2.3	Decanter Mass Balance . . . . .	162
	References. . . . .	164

<b>6</b>	<b>Discontinuous Batch Distillation</b> . . . . .	165
6.1	Differential Evaporation (Fig. 6.2) . . . . .	166
6.2	Batch Rectification [1–3] . . . . .	168
6.3	Technical Equipment . . . . .	176
6.4	Batch Stripper . . . . .	181
	References . . . . .	185
<b>7</b>	<b>Steam Distillation</b> . . . . .	187
7.1	Calculations of Steam Distillation [1] . . . . .	188
7.2	Required Stripping Steam Rate . . . . .	190
7.2.1	Required Stripping Steam Rate for One Liquid Phase (Fig. 7.2) . . . . .	190
7.2.2	Required Stripping Steam Rate for Two Liquid Phases (Fig. 7.3) . . . . .	195
7.3	Design of the Decanter for the Separation of Two Liquid Phases [2–4] . . . . .	199
7.3.1	Calculation of the Droplet Settling Velocities . . . . .	199
7.3.2	Dimensioning of the Decanter . . . . .	200
7.3.3	Setting of the Phase Height in the Decanter . . . . .	203
7.4	Stripping Steam Distributor Design [5] . . . . .	205
7.5	Design Example . . . . .	208
7.5.1	Required Stripping Steam Rate with Efficiency $\eta = 0.75$ . . . . .	208
7.5.2	Required Steam for Heating from 24 to 84°C and Evaporating the Toluene . . . . .	209
7.5.3	Evaporator Design . . . . .	209
7.5.4	Check on the Entrainment of Droplets . . . . .	210
7.5.5	Condenser Design for 450 Kg/H Toluene and 150 Kg/H Stripping Steam . . . . .	210
7.5.6	Decanter Design . . . . .	211
7.5.7	Stripping Steam Distributor Design . . . . .	212
	References . . . . .	213
<b>8</b>	<b>Absorption and Stripping Columns</b> . . . . .	215
8.1	Equilibria for the Design of Absorption and Desorption Columns . . . . .	215
8.1.1	Physical Equilibrium [1–3] . . . . .	215
8.1.2	Chemical Equilibrium [4, 5] . . . . .	223
8.2	Calculation of the Required Mass Transfer Units, $NTU_{OG}$ and $NTU_{OL}$ , Using the Slope $m$ of the Equilibrium Line . . . . .	228
8.3	Calculation of the Required Mass Transfer Units $NTU_{OG}$ or $NTU_{OL}$ Using the Logarithmic Partial Pressure or Concentration Difference . . . . .	229

8.3.1	Required Gas Side Mass Transfer Units $NTU_{OG}$ for Absorption. . . . .	229
8.3.2	Calculation of the Liquid Side Mass Transfer $NTU_{OL}$ for Desorption. . . . .	231
8.4	Calculation of the Required Theoretical Stages $NT$ for Absorption and Desorption. . . . .	232
8.4.1	Determination of the Theoretical Stages $NT$ for Absorption [9, 10]. . . . .	232
8.4.2	Calculation of the Theoretical Stages $NT$ for Desorption. . . . .	233
8.5	Conversion of the Required Mass Transfer Units $NTU_{OG}$ and $NTU_{OL}$ to the Required Number of Theoretical Trays $NT$ , and Vice Versa . . . . .	233
8.6	Determination of the Required Packing Height $H_{pack}$ . . . . .	234
8.7	Calculation of the Packing Height Using the Mass Transfer Number $K_{Ga}$ . . . . .	235
8.8	Calculation of the Required Theoretical Stages and the Concentrations on the Stages According to Nguyen [11, 12]. . . . .	237
8.8.1	Determination of the Required Ideal Number of Trays $N_{id}$ with a Tray Efficiency of $\eta_B = 1$ for Absorption. . . . .	237
8.8.2	Calculation of the Required Real Number of Trays $N_{real}$ with a Tray Efficiency of $\eta_V < 1$ for Absorption. . . . .	238
8.8.3	Determination of the Required Ideal Number of Trays $N_{idL}$ with $\eta_L = 1$ for Desorption . . . . .	239
8.8.4	Calculation of the Number of the Required Theoretical Trays with a Tray Efficiency of $\eta_L < 1$ for Desorption. . . . .	241
8.9	Graphical Determination of the Number of Stages for Absorption and Desorption. . . . .	242
8.10	Procedure for Absorber and Stripper Design for Linear Equilibrium and Operating Lines . . . . .	248
8.10.1	Design of an Absorption Column . . . . .	248
8.10.2	Design of a Desorption/Stripper Column. . . . .	259
8.11	Water Purification Air Stripper [13–16] . . . . .	263
8.12	Steam Stripper [17–21]. . . . .	267
8.12.1	Process Description . . . . .	267
8.12.2	Steam Stripper for the Stripping Out of Non-Water-Soluble Components from Water. . . . .	271
8.12.3	Steam Stripping of Non-Water-Soluble Materials with Water Phase Reflux. . . . .	273

8.13	Comparison of Air and Steam Strippers . . . . .	279
8.14	Ammonia Stripper . . . . .	282
8.15	Sour Gas Stripper [22] . . . . .	287
	References. . . . .	294
<b>9</b>	<b>Fluid Dynamic Dimensioning of Trays and Tray Efficiency. . . . .</b>	<b>295</b>
9.1	Fluid Dynamic Design Criteria. . . . .	295
9.1.1	Required Flow Cross Section for the Vapour Loading [1–7] . . . . .	299
9.1.2	Required Downcomer Cross Section for the Liquid [1–7] . . . . .	305
9.1.3	Required Column Diameter $D_K$ . . . . .	308
9.1.4	Flooding and Weeping in a Tray Column . . . . .	309
9.1.5	Pressure Drop Calculations [1–7] . . . . .	313
9.2	Efficiency of Cross Stream Trays . . . . .	320
	References. . . . .	327
<b>10</b>	<b>Fluid Dynamic Design of Random Packings and Structured Packings and the Determination of the HTU/HETP Values. . . . .</b>	<b>329</b>
10.1	Random Packed Columns. . . . .	329
10.1.1	Calculation Methods for the Pressure Loss in Random Packings [2–10]. . . . .	334
10.1.2	Calculation of the HTU and HETP Values [8–14] . . . .	338
10.2	Columns with Structured Packing. . . . .	357
	References. . . . .	362
<b>11</b>	<b>Demister Design. . . . .</b>	<b>365</b>
11.1	Why Use Demisters? . . . . .	366
11.2	Droplet Separation in Gravity, Wire Mesh, and Lamella Separators. . . . .	366
11.2.1	Allowable Gas Flow Velocities . . . . .	370
11.2.2	Liquid Capacity. . . . .	372
11.3	Vertical Demisters . . . . .	373
11.4	Horizontal Demisters . . . . .	374
11.5	Selection Criteria and Dimensioning. . . . .	379
11.6	Droplet Separation at High Pressures [6] . . . . .	382
11.7	Fog Separation in Fibre Filters or by Droplet Enlargement. . . .	390
11.7.1	Fog Separation in Fibre Filters . . . . .	390
11.7.2	Droplet Enlargement by Condensation . . . . .	391
	Appendix: Calculation of the Falling Velocity of Droplets in Air or Gas . . . . .	392
	References. . . . .	397

Practical Column Design Guide

Nitsche, M.; Gbadamosi, R.O.

2017, XIII, 397 p. 237 illus., 1 illus. in color., Hardcover

ISBN: 978-3-319-51687-5