

Contents

1	Introduction	1
1.1	Historical Evolution	1
1.2	CMOS Devices Scaling	3
1.3	High κ Dielectrics	5
1.3.1	Gadolinium Oxide	8
1.3.2	Scandium Oxide	8
1.3.3	Gadolinium Scandate	8
1.4	Metal Gate Electrodes	9
1.4.1	Scavenging Effect	9
1.5	Alternative Substrates	10
1.6	High Pressure Sputtering (HPS)	11
1.7	Alternatives Structures	12
1.8	Outline of the Thesis	13
	References	14
2	Fabrication Techniques	21
2.1	High Pressure Sputtering (HPS)	21
2.2	Glow Discharge Optical Spectroscopy (GDOS)	24
2.2.1	System I (Monocromator)	25
2.2.2	System II (Spectrometer)	26
2.3	Electron Beam (e-beam) Evaporation	27
2.3.1	SiO_x Acting as Field Oxide	29
2.3.2	Metallic Electrodes	29
2.4	Lithography Process	29
2.4.1	Positive Photoresist	30
2.4.2	Negative Photoresist	31
2.5	Rapid Thermal Annealing (RTA)	31
2.6	MIS Fabrication	32
2.6.1	Process Without Field Oxide (FOX)	32
2.6.2	Process with FOX	34

2.7	Substrates	36
2.7.1	Semiconductor Materials	36
2.7.2	Substrate Surface Cleaning	37
	References.	38
3	Characterization Techniques	41
3.1	Structural Characterization Techniques	42
3.1.1	Fourier Transform Infrared Spectroscopy (FTIR)	42
3.1.2	Grazing Incidence X Ray Diffraction (GIXRD)	45
3.1.3	X Ray Reflectometry (XRR).	46
3.1.4	X Ray Photoelectron Spectroscopy (XPS).	47
3.1.5	Transmission Electron Microscopy (TEM)	48
3.2	Electrical Characterization Techniques	49
3.2.1	MIS Capacitors	49
3.2.2	Capacitive Behavior of MIS Devices: $C-V_{gate}$ Characterization.	52
3.2.3	Interfacial State Density (D_{it}) Determination.	56
3.2.4	Leakage Current Density Measurements	59
	References.	60
4	Thermal Oxidation of Gd_2O_3	63
4.1	Experimental Method	63
4.2	Results and Discussion.	64
4.2.1	Plasma Characterization of Metallic Gd Sputtered in Ar.	64
4.2.2	Physical Characterization of the Thermally Oxidized GdO_x Films.	66
4.2.3	Electrical Characterization of MIS Devices with Thermally Oxidized Gd_2O_3	70
4.2.4	TEM Analysis of MIS Devices	72
4.3	Summary and Conclusions	74
	References.	74
5	Plasma Oxidation of Gd_2O_3 and Sc_2O_3	77
5.1	Experimental Method	77
5.2	Results and Discussion.	78
5.2.1	Feasibility of the Two-Step Deposition Process for Gd_2O_3 and Sc_2O_3	78
5.2.2	Optimization of the Two-Step Deposition Process for Gd_2O_3	87
5.2.3	Effect of FGA Temperature on Optimized MIS Devices with Plasma Oxidized Gd_2O_3	97
5.2.4	Electrical Characterization of Optimized MIS Devices with Plasma Oxidized Sc_2O_3	102

5.3	Summary and Conclusions	105
	References.	106
6	Gadolinium Scandate	109
6.1	Experimental Method	110
6.2	Results and Discussion	110
6.2.1	Plasma Characterization	110
6.2.2	Physical Characterization	111
6.2.3	Electrical Characterization.	115
6.3	Summary and Conclusions	122
	References.	122
7	Interface Scavenging	125
7.1	Experimental Method	125
7.2	Results and Discussion	126
7.2.1	Thick Ti Layers as Top Electrode with Gd_2O_3	126
7.2.2	Optimization of the Scavenging Effect for Plasma Oxidized Gd_2O_3	128
7.2.3	Scavenging Effect for Plasma Oxidized Sc_2O_3	134
7.2.4	Scavenging Effect for Plasma Oxidized $\text{Gd}_{0.9}\text{Sc}_{1.1}\text{O}_3$	136
7.3	Summary and Conclusions	138
	References.	139
8	Gd_2O_3 on InP Substrates	141
8.1	Experimental Method	141
8.2	Results and Discussion	142
8.2.1	Feasibility of Plasma Oxidized Gd_2O_3 Deposited on InP Substrates	142
8.2.2	Optimized Devices with Gd_2O_3 on InP.	145
8.2.3	Interface Scavenging with InP.	148
8.3	Summary and Conclusions	151
	References.	151
9	Conclusions and Future Work	155
9.1	Conclusions	155
9.2	Future Work	157
	Curriculum Vitae	159

Growth of High Permittivity Dielectrics by High Pressure
Sputtering from Metallic Targets

Pampillón Arce, M.Á.

2017, XXIII, 164 p. 116 illus., 6 illus. in color., Hardcover

ISBN: 978-3-319-66606-8