

Contents

Abstract	XI
Zusammenfassung	XV
Nomenclature	XIX
1 Introduction	1
1.1 Overview: silicon anodization	1
1.2 Objectives and outline of the work	3
2 State of the art	7
2.1 Introduction	7
2.2 Structuring techniques for semiconductor based smart systems	7
2.2.1 Principles and characteristics of structuring processes	9
2.2.2 Fabrication strategies for smart systems	10
2.2.3 Structuring techniques	12
2.2.4 Conclusions	18
2.3 Mass and charge transfer in silicon and electrolyte	19
2.3.1 Band diagram and transfer of charge and mass in bulk p-type silicon	19
2.3.2 Band diagram and transfer of charge and mass in bulk electrolyte	21
2.3.3 Interface silicon-electrolyte	25
2.4 Silicon anodization: current-voltage characteristics and dis- solution mechanisms	35
2.4.1 Cathodic polarization and open circuit	35
2.4.2 Pore formation	37
2.4.3 First and second plateaus of electropolishing	44
2.4.4 Position of the first and the second current peaks . . .	46
2.5 Silicon anodization: influence of process parameters	48

2.5.1	Current density	50
2.5.2	Etch time	54
2.5.3	Electrolyte mixture and concentration	58
2.5.4	Temperature	60
2.5.5	Substrate doping density	64
2.5.6	Crystal orientation	67
2.5.7	Conclusions	69
2.6	Application of silicon anodization for structuring	69
2.6.1	Fabrication aspects	69
2.6.2	Process flow for structuring with anodization process .	73
2.6.3	Shape control in anodization process	74
2.6.4	Structuring by pore formation (sacrificial porous silicon)	80
2.6.5	Structuring by electropolishing	81
2.7	Macroscale models of silicon anodization for structuring . . .	83
2.7.1	Charge flow models - primary and secondary current distribution	83
2.7.2	Mass transport and tertiary current distribution models	87
2.8	Conclusions on state of the art	89
3	Experimental, characterization and simulation methods	93
3.1	Fabrication methods	93
3.1.1	Electrolytes and other chemicals	93
3.1.2	Sample preparation	94
3.1.3	Sample anodization and post-processing	105
3.2	Characterization of samples	109
3.2.1	Mass measurement	109
3.2.2	Microscopic images	110
3.2.3	Surface quality characterization	111
3.2.4	Etch shape measurements	111
3.3	Macroscale simulations of the anodization process	114
3.3.1	Model geometry	114
3.3.2	Mesh configuration	116
3.3.3	Time-dependent solver configuration and stability issues	120
3.3.4	Further general model parameters	120
3.3.5	Specific parameters for secondary current distribution models	121
3.3.6	Hardware configuration	122
4	Microscale study of anodization process	125
4.1	Study of pore formation regime with full wafers	125

4.1.1	Current density sweep	126
4.1.2	Substrate resistivity sweep in the range 0.001–20 Ohm cm for p-type silicon	129
4.2	Extended study of pore formation and electropolishing regimes with small samples	132
4.2.1	Extended current density sweep in 29.93 m% HF with ethanol	132
4.2.2	Variation of HF concentration	139
4.2.3	Influence of porous silicon removal process on surface quality	141
4.3	Conclusions	142
5	Anodization process as a structuring technique	145
5.1	Process localization with frontside masking	145
5.1.1	Preliminary study	145
5.1.2	Influence of opening size and current density on time development of etch forms for low-doped p-type silicon	148
5.1.3	Influence of opening size and current density on etch forms for highly-doped p-type silicon	163
5.1.4	Proximity effects for neighboring openings for low- doped p-type silicon	170
5.1.5	Study of etch form development for pre-structured cavities	175
5.2	Process localization with backside local contacts	179
5.2.1	Etch form development for single circular backside contact	179
5.2.2	Influence of spacing between two backside rectangular openings on etch form	187
5.3	Combination of frontside masking and backside local contact	191
5.4	Macroscale simulation of anodization process	194
5.4.1	Primary current distribution model for low-doped p- type silicon	195
5.4.2	Primary current distribution model for highly-doped p-type silicon	207
5.4.3	Secondary current distribution model for low-doped p-type silicon	216
5.4.4	Secondary current distribution model for highly- doped p-type silicon	219
5.5	Conclusions	223

6	General conclusions	227
	Acknowledgments	231
	List of relevant publications	233
A	Appendix	239
A.1	Conversion of concentration units for aqueous HF electrolytes	239
A.1.1	Concentration units in chemistry	239
A.1.2	Reference data	241
A.1.3	HF:water solutions	242
A.1.4	HF:water:ethanol solutions	250
A.2	Conversions of other anodization parameters	256
A.2.1	Dissolution valence calculated from porosity and thickness of porous layer	256
A.2.2	Porosity and density of porous silicon	258
A.3	Experimental data	259
A.3.1	Experimental data for sec. 5.1.2	259
A.3.2	Comparison of the final current densities for sec. 5.1.3	264
A.4	Simulated data	265
A.4.1	Primary current distribution model for low-doped p-type silicon in sec. 5.4.1	265
A.4.2	Primary current distribution model for highly-doped p-type silicon in sec. 5.4.2	270
A.4.3	Secondary current distribution model for low-doped p-type silicon in sec. 5.4.3	273
A.4.4	Secondary current distribution model for highly-doped p-type silicon in sec. 5.4.4	276
	Bibliography	279

Silicon Anodization as a Structuring Technique

Literature Review, Modeling and Experiments

Ivanov, A.

2018, XXIX, 316 p. 141 illus., 3 illus. in color., Softcover

ISBN: 978-3-658-19237-2